

PRODUCT CODE

APL-S 400 4030

Round CRCA Die formed housing, powder coated white, grey or black surface finish. Opal PMMA diffuser. High efficient LEDs with optionally dimmable 1-10V and DALI. Mid power LEDs for uniform light distribution with CRI >80

TECHNICAL SPECIFICS

Lamp Description	30W LED
Color Temperature	3000K, 4000K, 6000K
Mounting Type	Surface, Suspended
Area	Indoor
IP Level	20

OPTICAL

Emission	Direct
Diffuser	High Efficiency Opal
Diffuser Material	PMMA

ELECTRICAL

Voltage	220-240v
---------	----------

HOUSING

Construction Material	CRCA
Diameter(mm)	400
Height(mm)	100
D	300-1500

ORDERING INFO

APL-S 400 4030 White	Non-Dimmable	3000k	30w
APL-S 400 4030 Black	Non-Dimmable	3000k	30w
APL-S 400 4030 Grey	Non-Dimmable	3000k	30w
APL-S 400 4030 White	Non-Dimmable	4000k	30w
APL-S 400 4030 Black	Non-Dimmable	4000k	30w
APL-S 400 4030 Grey	Non-Dimmable	4000k	30w
APL-S 400 4030 White	Non-Dimmable	6000k	30w
APL-S 400 4030 Black	Non-Dimmable	6000k	30w
APL-S 400 4030 Grey	Non-Dimmable	6000k	30w
APL-S 400 4030 White DALI	DALI Dimmable	3000, 4000, 6000	30w
APL-S 400 4030 Black DALI	DALI Dimmable	3000, 4000, 6000	30w
APL-S 400 4030 Grey DALI	DALI Dimmable	3000, 4000, 6000	30w
APL-S 400 4030 White 1-10v	1-10v Dimmable	3000, 4000, 6000	30w
APL-S 400 4030 Black 1-10v	1-10v Dimmable	3000, 4000, 6000	30w
APL-S 400 4030 Grey 1-10v	1-10v Dimmable	3000, 4000, 6000	30w

