

PRODUCT CODE

APL-S 500 5045

Round CRCA Die formed housing, powder coated white, grey or black surface finish. Opal PMMA diffuser. High efficient LEDs with optionally dimmable 1-10V and DALI. Mid power LEDs for uniform light distribution with CRI >80

TECHNICAL SPECIFICS

Lamp Description	45W LED
Color Temperature	3000K, 4000K, 6000K
Mounting Type	Surface, Suspended
Area	Indoor
IP Level	20

OPTICAL

Emission	Direct
Diffuser	High Efficiency Opal
Diffuser Material	PMMA

ELECTRICAL

Voltage	220-240v
---------	----------

HOUSING

Construction Material	CRCA
Diameter(mm)	500
Height(mm)	100
D	300-1500

ORDERING INFO

APL-S 500 5045 White	Non-Dimmable	3000k	45W
APL-S 500 5045 Black	Non-Dimmable	3000k	45W
APL-S 500 5045 Grey	Non-Dimmable	3000k	45W
APL-S 500 5045 White	Non-Dimmable	4000k	45W
APL-S 500 5045 Black	Non-Dimmable	4000k	45W
APL-S 500 5045 Grey	Non-Dimmable	4000k	45W
APL-S 500 5045 White	Non-Dimmable	6000k	45W
APL-S 500 5045 Black	Non-Dimmable	6000k	45W
APL-S 500 5045 Grey	Non-Dimmable	6000k	45W
APL-S 500 5045 White DALI	DALI Dimmable	3000, 4000, 6000	45W
APL-S 500 5045 Black DALI	DALI Dimmable	3000, 4000, 6000	45W
APL-S 500 5045 Grey DALI	DALI Dimmable	3000, 4000, 6000	45W
APL-S 500 5045 White 1-10v	1-10v Dimmable	3000, 4000, 6000	45W
APL-S 500 5045 Black 1-10v	1-10v Dimmable	3000, 4000, 6000	45W
APL-S 500 5045 Grey 1-10v	1-10v Dimmable	3000, 4000, 6000	45W

