

PRODUCT CODE

APP-R 600 6056

Round CRCA Die formed housing, powder coated white, grey or black surface finish. Opal PMMA diffuser. High efficient LEDs with optionally dimmable 1-10V and DALI. Mid power LEDs for uniform light distribution with CRI >80



TECHNICAL SPECIFICS

Lamp Description	56W LED
Color Temperature	3000K, 4000K, 6000K
Mounting Type	Recessed
Area	Indoor
IP Level	20



OPTICAL

Emission	Direct
Diffuser	High Efficiency Opal
Diffuser Material	PMMA

ELECTRICAL

Voltage	220-240v
---------	----------

HOUSING

Construction Material	CRCA
Diameter(mm)	600
Height(mm)	100
D	300-1500

ORDERING INFO

APP-R 600 6056 White	Non-Dimmable	3000k	56W
APP-R 600 6056 Black	Non-Dimmable	3000k	56W
APP-R 600 6056 Grey	Non-Dimmable	3000k	56W
APP-R 600 6056 White	Non-Dimmable	4000k	56W
APP-R 600 6056 Black	Non-Dimmable	4000k	56W
APP-R 600 6056 Grey	Non-Dimmable	4000k	56W
APP-R 600 6056 White	Non-Dimmable	6000k	56W
APP-R 600 6056 Black	Non-Dimmable	6000k	56W
APP-R 600 6056 Grey	Non-Dimmable	6000k	56W
APP-R 600 6056 White DALI	DALI Dimmable	3000, 4000, 6000	56W
APP-R 600 6056 Black DALI	DALI Dimmable	3000, 4000, 6000	56W
APP-R 600 6056 Grey DALI	DALI Dimmable	3000, 4000, 6000	56W
APP-R 600 6056 White 1-10v	1-10v Dimmable	3000, 4000, 6000	56W
APP-R 600 6056 Black 1-10v	1-10v Dimmable	3000, 4000, 6000	56W
APP-R 600 6056 Grey 1-10v	1-10v Dimmable	3000, 4000, 6000	56W